

On-premises laundries face enough daily challenges, wrestling with complicated, inefficient equipment shouldn't be one of them. IPSO's IPD 50 and 75 lb tumblers combine an ultra-efficient design with a user-friendly microprocessor control to stream-line the laundry process. Our goal is building equipment that's simple to own and even more simple to operate.

Simplifying Ownership

EFFICIENT DRYING. IPSO tumblers perfectly balance heat, airflow and cylinder design, which translates into the most efficient drying process. That means utility costs are kept low.

TIME SAVINGS. A large, self-cleaning lint screen means less cleaning and ensures efficient operation. Self-adjusting belts save time and reduce maintenance costs.

LARGE CAPACITY. While many laundries experience bottlenecks in the drying process, the large 50 and 75 lb capacity of IPD tumblers combined with their efficiency keep your laundry's productivity at its highest level.

PEACE OF MIND. Our commitment to you comes with a 3-year parts warranty.

SIMPLE CONTROLS. The microprocessor control is easy to train staff to operate and offers five preset drying cycles for greater operating ease. It also delivers flexibility with simple customization of cycles.



RUGGED CONSTRUCTION. Tumblers in on-premises laundries receive their share of heavy-use abuse. IPSO's rugged design and heavy-duty door and hinge can take whatever your staff dishes out.

THE BOTTOM LINE. It's the balance between airflow, heat and drop that leads to fast and efficient drying.

Because of their size, efficiency and simple control, IPSO IPD 50 and 75 lb drying tumblers will have the ultimate impact on your laundry's productivity and bottom line. Put simply, IPSO gets results.

IPD50 - 50 lb Tumbler*
IPD75 - 75 lb Tumbler*

* IPSO also offers 25, 30, 35, 55 lb Single Tumblers and 30 and 45 lb Stack Tumblers



IPD 50 - 75 lb Tumbler Specifications

	IPD50			IPD75			
Capacity - lb (kg)	50 (23)			75 (34)			
Height - in (mm)	76 5/8" (1946)			76 5/8" (1946)			
Width - in (mm)	38 5/8" (981)			38 5/8" (981)			
Depth - in (mm)	47" (1194)			53" (1346)			
Net Weight - lb (kg)	545 (247)			615 (279)			
Shipping Weight - lb (kg)	602 (273)			677 (307)			
Cylinder Dimensions	Diameter - in (mm)	37" (939)		37" (940)			
	Depth - in (mm)	30" (762)		36" (914)			
	Volume - cu.ft. (liters)	18.6 (528)		22.4 (634)			
Airflow - cfm (liters/sec.)	Gas, Steam & Electric Models 750 (354)			Gas & Steam Models 920 (434) Electric Models 750 (354)			
Plumbing Connections	Gas Models 1/2" NPT Steam Models 3/4" NPT			Gas Models 1/2" NPT Steam Models 3/4" NPT			
Energy Data	Btu/hr (kcal/hr)	Gas Models	120,000 (30,240)		Gas Models 165,000 (41,580)		
		Steam Models	5.1		Steam Models 6.1		
	BHP@100 psi kW	Electric Models	30		Electric Models 30		
Electrical Specifications*	Gas & Steam Models	Serial Plate (Amps)	Non Rev	Rev	Gas & Steam Models	Serial Plate (Amps)	
			Non Rev	Rev			Non Rev
	120/60/1	9.3	-	120/60/1	13.8	-	
	200-208/240/60/1	5.1	-	200-208/240/60/1	7.6	-	
	200-208/240/60/3	2.8	2.8	200-208/240/60/3	3.8	4.3	
	460-480/60/3	1.4	1.9	460-480/60/3	1.9	2.1	
	Electric Models	208/60/3	89	88	208/60/3	89	88
		240/60/3	79	78	240/60/3	79	78
480/60/3		38	38	480/60/3	38	38	
Shipping Dimensions		Width - in (mm) 41 1/2" (1054) Depth - in (mm) 52 1/8" (1323) Height - in (mm) 81" (2057)			Width - in (mm) 41 1/2" (1054) Depth - in (mm) 56 7/16" (1433) Height - in (mm) 81" (2057)		
Agency Approvals	Gas	CSA, CE		CSA, CE			
	Steam	CSA, CE		CSA, CE			
	Electric	CSA, CE		CSA, CE			

* Tumbler models are made to suit a variety of electrical service characteristics. See your IPSO distributor for specifications.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

© Copyright 2008 Alliance Laundry Systems, LLC

Printed in the U.S.A.

Questions? Contact us at:
1 800 USA IPSO or www.ipso.com
1 800 (872-4776)

Control Options



Dual Digital Control



DMP Control

